



INTERNATIONAL STANDARD



Plugs and socket-outlets for household and similar purposes – Part 1: General requirements

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.120.30

ISBN 978-2-8322-3990-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	6
1 Scope	8
2 Normative references	9
3 Terms and definitions	10
4 General requirements	18
5 General remarks on tests	18
6 Ratings	20
7 Classification	21
8 Marking	23
9 Checking of dimensions	27
10 Protection against electric shock	29
11 Provision for earthing	35
12 Terminals and terminations	37
13 Construction of fixed socket-outlets	57
14 Construction of plugs and portable socket-outlets	68
15 Interlocked socket-outlets	76
16 Resistance to ageing, protection provided by enclosures, and resistance to humidity	77
17 Insulation resistance and electric strength	84
18 Operation of earthing contacts	85
19 Temperature rise	85
20 Breaking capacity	94
21 Normal operation	98
22 Force necessary to withdraw the plug	102
23 Flexible cables and their connection	107
24 Mechanical strength	114
25 Resistance to heat	133
26 Screws, current-carrying parts and connections	136
27 Creepage distances, clearances and distances through sealing compound	138
28 Resistance of insulating material to abnormal heat, to fire and to tracking	140
29 Resistance to rusting	145
30 Additional tests on pins provided with insulating sleeves	145
31 EMC requirements	147
32 Electromagnetic fields (EMF) requirements	148
Annex A (normative) Safety-related routine tests for factory-wired portable accessories (protection against electric shock and correct polarity)	149
Annex B (informative) Alternative gripping tests	151
Annex C (normative) Switches incorporated in portable socket-outlets	154
Annex D (normative) Requirements for plugs and fixed or portable socket-outlets intended to be used with AWG cables	155
Annex E (informative) Tests to be applied during the production of crimped connections in accessories	168

Annex F (normative) Additional requirements for accessories provided with insulation-piercing terminals	170
Annex G (informative) Additional tests and requirements for accessories intended to be used in ambient temperatures below –5 °C down to and including –45 °C.....	180
Annex H (informative) Additional tests and requirements for accessories intended to be used in ambient temperatures above +40 °C up to and including +70 °C.....	185
Annex I (normative) Additional requirements and tests for plugs and socket-outlets for high-load (HL) application	188
Bibliography.....	195
Figure 1 – Examples of accessories.....	11
Figure 2 – Example of thread-forming screw	14
Figure 3 – Example of thread-cutting screw	14
Figure 4 – Examples of membranes and grommets	16
Figure 5 – Test piston dimensions.....	27
Figure 6 – Arrangement for compression test.....	30
Figure 7 – Gauge for checking non-accessibility of live parts, through shutters	33
Figure 8 – Gauge for checking non-accessibility of live parts, through shutters, and of live parts of socket-outlets with increased protection.....	34
Figure 9 – Pillar terminals	40
Figure 10 – Screw head terminals and stud terminals	41
Figure 11 – Saddle terminals	42
Figure 12 – Mantle terminals.....	43
Figure 13 – Arrangement for checking damage to conductors	44
Figure 14 – Information for deflection test.....	55
Figure 15 – Verification of the requirements of 13.4	61
Figure 16 – Device for checking the resistance to lateral strain	65
Figure 17 – Device for testing pins which are not solid.....	69
Figure 18 – Types of test wall	81
Figure 19 – Test set-up in accordance with 16.2.3	82
Figure 20 – Clamping unit for the temperature rise test of Clause 19	89
Figure 21 – Example of a trend line calculation.....	94
Figure 22 – Example of apparatus for breaking capacity and normal operation test.....	96
Figure 23 – Circuit diagrams for breaking capacity and normal operation tests	97
Figure 24 – Test procedures for normal operation for socket-outlets with shutters (see Clause 21)	101
Figure 25 – Apparatus for verification of maximum withdrawal force	104
Figure 26 – Gauge for the verification of minimum withdrawal force	105
Figure 27 – Apparatus for testing cord retention.....	108
Figure 28 – Apparatus for flexing test	113
Figure 29 – Sketches showing the application of the blows according to Table 23.....	118
Figure 30 – Apparatus for impact test at low temperature of 24.5.....	121
Figure 31 – Apparatus for abrasion test on insulating sleeves of plug pins	122
Figure 32 – Arrangement for mechanical strength test on multiple portable socket-outlets	124

Figure 33 – Example of test arrangement to verify the retention of pins in the body of the plug	125
Figure 34 – Arrangement for test on covers or cover-plates	128
Figure 35 – Gauge (thickness about 2 mm) for the verification of the outline of covers or cover-plates.....	129
Figure 36 – Examples of application of the gauge of Figure 35 on covers fixed without screws on a mounting surface or supporting surface	130
Figure 37 – Examples of application of the gauge of Figure 35 in accordance with the requirements of 24.16	131
Figure 38 – Gauge for verification of grooves, holes and reverse tapers	132
Figure 39 – Sketch showing the direction of application of the gauge of Figure 38	132
Figure 40 – Ball pressure test apparatus.....	134
Figure 41 – Apparatus for compression test for the verification of resistance to heat specification of 25.5	135
Figure 42 – Diagrammatic representation of 28.1.2	142
Figure 43 – Apparatus for testing resistance to abnormal heat of insulating sleeves of plug pins	144
Figure 44 – Apparatus for pressure test at high temperature	146
Figure 45 – Impact test apparatus on pins provided with insulating sleeves	147
Figure B.1 – Reference plug for gripping test.....	152
Figure B.2 – Example of the test apparatus for plug gripping test.....	153
Figure F.1 – Example of IPTs.....	178
Figure F.2 – Example of test-points	178
Figure F.3 – Temperature cycle for voltage drop test 12.4.11	179
Figure H.1 – Schematic drawing of a de-rating curve with an example of a de-rated current I_d at the operating ambient temperature t_d	186
Table 1 – Survey of specimens needed for tests	19
Table 2 – Preferred combinations of types and ratings	21
Table 3 – Gauge tolerances	28
Table 4 – Relationship between rated current and connectable nominal cross-sectional areas of copper conductors.....	38
Table 5 – Values for pull test for screw-type terminals	45
Table 6 – Composition of conductors	46
Table 7 – Tightening torques for the verification of the mechanical strength of screw-type terminals	48
Table 8 – Relationship between rated current and connectable cross-sectional areas of copper conductors for screwless-type terminals	49
Table 9 – Value for pull test for screwless-type-type terminals	51
Table 10 – Values for flexing under mechanical load test for copper conductors	52
Table 11 – Test current for the verification of electrical and thermal stresses in normal use for screwless-type terminals	52
Table 12 – Nominal cross-sectional areas of rigid copper conductors for deflection test of screwless-type terminals.....	55
Table 13 – Deflection test forces for screwless-type terminals	56
Table 14 – Forces to be applied to covers, cover-plates or actuating members whose fixing is not dependent on screws	63

Table 15 – External cable dimension limits for surface-type socket-outlets	67
Table 16 – Nominal cross-sectional areas of copper conductors for the temperature-rise test	86
Table 17 – Test current for cycling tests on accessories with crimped connection	93
Table 18 – Relationship between rating of accessories, nominal cross-sectional areas of test conductors and test currents for the tests of temperature rise (Clause 19) and normal operation (Clause 21).....	99
Table 19 – Maximum and minimum withdrawal force for plugs and socket-outlets	106
Table 20 – External dimensions of flexible cables to be accommodated by cord anchorages	109
Table 21 – Torque test values for cord anchorages	110
Table 22 – Maximum dimensions of flexible cables to be accommodated in rewirable accessories	111
Table 23 – Height of fall for impact tests	116
Table 24 – Torque test values for cable glands	122
Table 25 – Resistance to heat of different types or parts of accessories	133
Table 26 – Creepage distances, clearances and distances through insulating sealing compound	139
Table A.1 – Diagrammatic representation of routine tests to be applied to factory-wired portable accessories	150
Table F.1 – Relationship between rated currents and connectable cross-sectional areas of copper conductors for IPTs	173
Table F.2 – Test current for the verification of electrical and thermal stresses in normal use of IPTs	177
Table G.1 – Energy for impact tests	183
Table I.1 – Test current for cycling tests on plugs	192

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PLUGS AND SOCKET-OUTLETS FOR HOUSEHOLD AND SIMILAR PURPOSES –

Part 1: General requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60884-1 has been prepared by subcommittee 23B: Plugs, socket-outlets and switches, of IEC technical committee 23: Electrical accessories. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2002, Amendment 1:2006 and Amendment 2:2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) plugs and socket-outlets incorporating pilot lights;
- b) crimped connections in accessories;
- c) insulation piercing terminals (IPT);
- d) accessories to be used with American Wire Gauge (AWG) cables;
- e) accessories used in T° below –5 °C down to and including –45 °C;
- f) accessories used in T° above +40 °C up to and including +70 °C;

- g) plugs and socket-outlets for high load (HL);
- h) clarification of some definitions;
- i) durability of markings test;
- j) introduction of thermal monitoring in the plug;
- k) requirements for shutters in portable socket-outlets;
- l) test walls for the verification of ingress of water;
- m) rewriting of the temperature rise clause.

The text of this International Standard is based on the following documents:

Draft	Report on voting
23B/1386/FDIS	23B/1400/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 60884 series, published under the general title *Plugs and socket-outlets for household and similar purposes*, can be found on the IEC website.

The following print types are used:

- requirements: in roman type;
- test specifications: in *italic* type;
- notes: in small roman type.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

The contents of the corrigendum 1 (2023-12) have been included in this copy.

PLUGS AND SOCKET-OUTLETS FOR HOUSEHOLD AND SIMILAR PURPOSES –

Part 1: General requirements

1 Scope

This part of IEC 60884 applies to plugs and fixed or portable socket-outlets for AC only, with or without earthing contact, with a rated voltage greater than 50 V but not exceeding 440 V and a rated current not exceeding 32 A, intended for household and similar purposes, either indoors or outdoors.

Compatible plugs and socket-outlets, when combined, form a plug and socket-outlet system. Standardized systems used around the world are reported in IEC/TR 60083.

The rated current is limited to 16 A maximum for accessories provided with screwless-type terminals.

This document covers only those requirements for mounting boxes which are necessary for the tests on the socket-outlet.

NOTE 1 Requirements for general purpose mounting boxes are given in IEC 60670-1.

This document also applies to:

- plugs which are a part of cord sets;
- plugs and portable socket-outlets which are a part of cord extension sets;
- plugs and socket-outlets which are a component of an appliance, unless otherwise stated in the standard for the relevant appliance; and
- plugs and socket-outlets incorporating pilot lights.

This document does not apply to:

- plugs, socket-outlets and couplers for industrial purposes;
- appliance couplers;
- plugs, fixed and portable socket-outlets for extra low voltage (ELV);

NOTE 2 ELV values are specified in IEC 60364-4-41.

- fixed socket-outlets combined with fuses, automatic switches, etc.

Plugs of this document are intended to be energised by socket-outlets.

NOTE 3 Use in any other manner could result in unsafe conditions within the installation if proper precautions are not taken. When energy producing equipment is connected to the fixed installation via plugs of this document all safety aspects of the products and the installation need to be evaluated by the manufacturer of the energy producing equipment.

Plugs and socket-outlets complying with this document are suitable for use at ambient temperatures not normally exceeding +40 °C, but their average temperature over a period of 24 h does not exceed +35 °C, with a lower limit of the ambient air temperature of –5 °C.

In locations where special conditions prevail, such as in ships, vehicles and the like and in hazardous locations, for example where explosions are liable to occur, additional requirements can be applicable.

This document gives additional requirements for accessories intended to be used with AWG cables, see Annex D (normative).

This document gives additional tests to be applied during the production of crimped connections in accessories, see Annex E (informative).

This document gives additional requirements for accessories provided with insulation-piercing terminals, see Annex F (normative).

This document gives additional specifications for accessories intended to be used in ambient temperatures below –5 °C down to and including –45 °C, see Annex G (informative).

This document gives additional specifications for accessories intended to be used in ambient temperatures above +40 °C up to and including +70 °C, see Annex H (informative).

This document gives additional requirements for plugs and socket-outlets for high load (HL). These plugs and socket-outlets are typically intended to be used for loads applying long and repetitive cycles up to the rated current of the accessories, see Annex I (normative).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-30, *Environmental testing – Part 2-30: Tests – Test Db: Damp heat, cyclic (12 + 12 h cycle)*

IEC 60068-2-31, *Environmental testing – Part 2-31: Tests – Test Ec: Rough handling shocks, primarily for equipment-type specimens*

IEC 60068-2-75, *Environmental testing – Part 2-75: Tests – Test Eh: Hammer tests*

IEC 60112, *Method for the determination of the proof and the comparative tracking indices of solid insulating materials*

IEC 60227 (all parts), *Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V*

IEC 60245 (all parts), *Rubber insulated cables – Rated voltages up to and including 450/750 V*

IEC 60417, *Graphical symbols for use on equipment* (available at <http://www.graphical-symbols.info/equipment>)

IEC 60423:2007, *Conduit systems for cable management – Outside diameters of conduits for electrical installations and threads for conduits and fittings*

IEC 60529:1989, *Degrees of protection provided by enclosures (IP Code)*

IEC 60529:1989/AMD1:1999

IEC 60529:1989/AMD2:2013

IEC 60669 (all parts), *Switches for household and similar fixed-electrical installations*

IEC 60669-2-1:2021, *Switches for household and similar fixed electrical installations – Part 2-1: Particular requirements – Electronic control devices*

IEC 60695-2-10:2021, *Fire hazard testing – Part 2-10: Glowing/hot-wire based test methods – Glow-wire apparatus and common test procedure*

IEC 60695-2-11:2021, *Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end products (GWEPT)*

IEC 60884-2-1, *Plugs and socket-outlets for household and similar purposes – Part 2-1: Particular requirements for fused plugs*

IEC 61032:1997, *Protection of persons and equipment by enclosures – Probes for verification*

IEC 61058 (all parts), *Switches for appliances*

IEC 61545, *Connecting devices – Devices for the connection of aluminium conductors in clamping units of any material and copper conductors in aluminium bodied clamping units*

ISO/IEC Guide 51, *Safety aspects – Guidelines for their inclusion in standards*

ISO 1456:2009, *Metallic and other inorganic coatings – Electrodeposited coatings of nickel, nickel plus chromium, copper plus nickel and of copper plus nickel plus chromium*

ISO 2081:2018, *Metallic and other inorganic coatings – Electroplated coatings of zinc with supplementary treatments on iron or steel*

ISO 2093:1986, *Electroplated coatings of tin – Specification and test methods*