and methods

Fechnical data

Technical data and methods: Machinery 01

Machinery/related product name: Machinery 01

> **Product:** M. - Machinery

Type/model: Type/model

Batch/serial number: Batch/serial number

> **Revision:** 00 - 08.11.2025

Year of construction: 2025

> Regulation (EU): Regulation (EU) 2023/1230 (EN)

Manufacturer: Manufacturer Intended purpose: Intended purpose **Description:** Description

Certification Procedure

The machinery does not complies Annex I

- Internal production control (module A) Annex VI.

CE Marking Process

Risk assessment

Tool | Classic

The risk assessment is carried out on the EHSR of Annex III of the Regulation (EU) 2023/1230.

EN ISO 12100

Safety of machinery - General principles for design - Risk assessment and risk reduction

ISO/TR 14121-2

Safety of machinery - Risk assessment - Part 2: Pratical guidance and examples of methods

The hybrid tool is described in section 6.5 of ISO/TR 14121-2. The hybrid tool combines two of the methods described in the ISO/TR 14121-2. They are usually risk charts (qualitative tool) combined with matrices or scoring systems (quantitative method). The risk factors to be taken into consideration are the same as the tree method (gravity, frequency, probability, and avoidability) and each of them contains different levels to which correspond to different numerical weights. The method is applied as follows:

- 1. to estabilish the numerical weights for the severity, the frequency, the probability and the avoidability of the damage (see below the tables with the relative numerical weights);
- 2. add the three frequency, probability, and avoidance weights to determine the probability class "CI" (Class) (CI = Fr + Pr + Av);
- 3. insert the Gravity and Class dimensions into a weighting matrix;
- 4. calculate the risk by finding the intersection point of the row (Cl) with the column (Se) of the matrix.

Consequences / Severity		Class CI (Fr+Pr+Av)				Frequency		Probability		Avoidance	
(Se)	4	5-7	8-10	11-13	14-15	(Fr)		(Pr)		(Av)	
Death, losing an eye or arm	4					<= 1h	5	Very high	5		
Permanent, losing fingers	3					> 1h to <= 24h	5	Likely	4		
Reversible, medical attention	2	?				> 24 to <= 2w	4	Possible	3	Impossible	5
Reversible, first aid	1					> 2w to <= 1y	3	Rarely	2	Possible	3
						> 1y	2	Negligible	1	Likely	1



Project	Machinery		Year	
Report Reg. (EU) 2023/1230 EN	Machinery 01		2025	
Certifico S.r.l.	Type/model	Batch/serial number	00	